

DISPATCH

BACTERIA REINFORCED ENZYMES



DESCRIPTION

DISPATCH is a synergistic blend of bacterial strains and a fortified enzyme system which insure rapid break down of grease, fat, proteins, cellulose and other complex organic materials. This unique enzyme system reinforces the bacterial cultures to instantly go to work liquefying organic waste found in drain lines, grease traps, septic tanks, wet wells and lift stations. **DISPATCH** contains no harsh acids or caustics, making it ideal for kitchen sinks, garbage disposals, bathroom drains or anywhere organic waste is a problem. This powerful technology will provide consistent performance and is safe to use and safe for the environment.

BENEFITS - FEATURES

- * Extremely powerful
- * Instant odor control
- * Activates drain lines & grease traps
- * Solubilizes grease
- * Activates immediately
- * Biodegradable
- * Non-toxic
- * Non-caustic

ADVANTAGES

- * Digests and liquefies waste
- * Helps remove stains and odors
- * Non-acid

WHERE TO USE

- * Drain Lines
- * Porta-toilets
- * Restrooms
- * Grease Traps
- * Septic Tanks
- * Dumpsters

RECOMMENDED FOR

- * Waste Treatment Plants
- * Food Service
- * Hospitals
- * Health Care Facilities
- * Food Processing Plants
- * Refuse Hauler
- * Manufacturing Plants
- * Office Buildings
- * Athletic Clubs
- * Country Clubs
- * Schools
- * Animal Shelters
- * Apartment Complexes
- * Veterinary Clinics

DIRECTIONS

METER STICK: Follow instructions furnished with equipment.

SINKS, FLOOR DRAINS, URINALS & TOILETS: Use 2 ounces of **DISPATCH** once per week in every drain and allow to work overnight. For drains that receive large amounts of organic matter (kitchen, floor drains, laundry sinks) increase the treatment to 4-6 ounces as often as every other day. For best results treat at the end of the day or periods of lowest flow. To prevent loosened debris from causing obstructions always begin the treatment program by treating the drains closest to the main line. Bleach, harsh drain openers and disinfectant may kill bacterial. Allow several hours after the use of these products then retreat with **DISPATCH**.

GREASE TRAP TREATMENT: For average sized grease traps (about 20 cubic feet capacity) add one quart directly to the trap or through the drain. Then use one pint per week for maintenance.

SEWER LATERAL TREATMENT: Laterals are treated during periods of low flow by adding through man holes. Dosage per unit length of lateral will vary with the diameter of the line.

Lateral Diameter (inches)	Ounces/500 Feet
8 Inches	32 Ounces
12 Inches	48 Ounces
16 Inches	64 Ounces
20 Inches	96 Ounces
24 Inches	128 Ounces

SEPTIC TANK TREATMENT: Use 2-4 quarts of **DISPATCH** for initial treatment of a 500 gallon tank. The weekly maintenance dose should be one pint for each 5 people using the system.

WET WELLS AND LIFT STATIONS: Add 1 quart per 500 cubic feet directly into wet well.

Caution: Contains live bacteria cultures and enzymes. May cause skin irritation. Wash after handling. Store this product at temperatures above 32 degrees and below 100 degrees.

SPECIFICATIONS

Color.....Milky White	Specific gravity.....1.010	Density.....Heaver than air
Odor.....Bland	Flash point.....N/A	Volatile.....80+
pH.....7.5 to 8.5	Boiling Point.....212F	Shelf Life.....1 year

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

