

GLEAM

METALLIC INTERLOCKED, POLYMER FLOOR FINISH



DESCRIPTION

This medium-solids, acrylic polymer, metal cross linked floor finish provides an extraordinary value. This time-proven favorite has **outstanding gloss**, provides **excellent wear**, and is **highly resistant to black heel marks**. It meets or exceeds ASTM Standards for **slip resistance**. In addition, it provides a **durable coating** that **responds well to varied maintenance program procedures**. It may be spray buffed with either low or high-speed equipment, or mopped-on restoration with high-speed burnishing can be used. Furthermore, this product is easily removed with either conventional or no-rinse strippers.

BENEFITS - FEATURES

- * Durability
- * Appearance
- * High-gloss
- * Self-leveling
- * Versatile
- * Excellent wear
- * Resists black marks

ADVANTAGES

- * Extended wear and superior protection
- * Never yellows
- * May be used with or without floor sealer
- * Use on all resilient flooring as well as terrazzo, sealed wood, and some hard tile surfaces

WHERE TO USE

- * Resilient Flooring
- * Terrazzo
- * Sealed Wood Flooring
- * Linoleum

RECOMMENDED FOR

- * Schools
- * Hospitals
- * Show Rooms
- * Restaurants
- * Shopping Malls
- * Office Buildings
- * Motels
- * Airports
- * Hotels
- * Nursing Homes
- * Institutions
- * Cafeterias
- * Public Buildings
- * Government Buildings
- * Churches
- * Athletic & Country Clubs

DIRECTIONS

1. Strip all old wax or finish. Rinse if necessary and allow to dry.
2. Apply a uniform coat of finish with a clean mop applicator.
3. Allow to dry for 20-30 minutes before applying subsequent coats.

4. Apply a sufficient number of coats to provide adequate protection for the floor.

No maintenance program will work efficiently without an effective level of protection.

Requires no authorization by USDA prior to its use in offices and other similar non processing areas.

SPECIFICATIONS

Fragrance.....Mild	Density.....8.4 lb./gal.	Freeze/thaw stability.....3 cycles
Gloss.....Excellent	Leveling.....Excellent	Drying time.....20-30 min.
pH.....8.7	Recoatibility.....Very good	Coverage.....3,000-4,000 sq. ft./gal.
Shelf life.....2 yrs. min.	Heel mark resistance.....Very good	Slip resistance (James machine).....(.61-.65)

Another Exclusive Product of

ULTRA-CHEM, INC.

Kansas City - Phoenix 800-451-0726

