LOCK IT



METAL INTERLOCKED, ACRYLIC POLYMER FLOOR SEALER

DESCRIPTION

Before applying your floor finish or wax, this acrylic sealer is one of the wisest investments you can make. It is **very hard, durable,** & **detergent-resistant;** therefore, making it really tough! It may be used on all types of resilient tile, concrete, wood, terrazzo, and marble. Best of all, this product will save you money because it **seals the pores in the floor;** therefore, **less finish and wax is used.** Furthermore, it continues to protect your floor even after all finish and wax has been worn away. Not only will it protect your floors for years, but its **high-gloss** will **never yellow or powder.** In addition, it is compatible with every water-based finish or wax.

BENEFITS - FEATURES

- * Durable
- * Easy to apply
- * Compatible

- * Versatile
- * High-gloss

ADVANTAGES

- * Acrylic polymer provides long-lasting protection
- * Won't yellow or powder
- * Compatible with all water-based finishes or waxes
- * Enhances the appearance of the finish

WHERE TO USE

- * Terrazzo
- * Concrete
- * Steel
- * Asphalt
- * Vinyl
- * Marble
- * Resilient Tile
- * Sealed Wood
- * Rubber
- * Linoleum
- * Vinyl Asbestos

RECOMMENDED FOR

- * Schools
- * Hospitals
- * Show Rooms
- * Restaurants
- * Shopping Malls
- * Office Buildings
- * Motels
- * Airports

- * Hotels
- * Nursing Homes
- * Institutions
- * Cafeterias
- * Public Buildings
- * Government Buildings
- * Churches
- * Athletic & Country Clubs

DIRECTIONS

Start with a very clean, dry, stripped floor. Apply a uniform coat of sealer with clean applicator or mop. Let dry for at least 30 minutes before applying a second coat. A third coat may be necessary on worn floors. Apply finish or wax on top of sealer for lasting beauty and protection.

Sealer may be damp mopped, spray buffed, or high-speed buffed.

Requires no authorization by USDA prior to its use in offices and other similar nonprocessing areas.

SPECIFICATIONS

Fragrance	Characteristic
Color	Milky white
pH	8.7
Shelf life	2 vrs. min.

Color (dried film)	Clear
Leveling	Excellent
Coverage	2,000 sq. ft./gallon
Flash point	None

Density (lbs./gal.)	8.4
Nonvolatile solids	16%
Total actives	18.9%

Another Exclusive Product of



