

SAFETY DATA SHEET

Date Prepared : 5/21/2015
SDS No : Dyna Foam_SDS
Date Revised : 6/2/2015
Revision No : 2

Dyna-Foam

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Dyna-Foam
GENERAL USE: Foaming Decarbonate
PRODUCT CODE: F10-25020

MANUFACTURER

Ultra-Chem Inc.
8043 Flint
Lenexa, KS 66214

Emergency Phone: 913-492-2929

Customer Service: 800-451-0726

Transportation: 800-535-5053

24 HR. EMERGENCY TELEPHONE NUMBERS

Infotrac 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion / Irritation, Category 1
Serious Eye Damage / Eye Irritation, Category 1

GHS LABEL

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)



Corrosion

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENTS

Prevention:

P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash face, hands and any exposed skin thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P310: Immediately call a POISON CENTER or doctor/physician.

Storage:

P102: Keep out of reach of children.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
2- Butoxyethanol	< 10	111-76-2
Potassium Hydroxide	< 10	1310-58-3

4. FIRST AID MEASURES

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or Poison Control Center Immediately.

SKIN: Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. Call a POISON CENTER or doctor / physician. Remove and wash contaminated clothing before re-use.

INGESTION: Rinse mouth. Do NOT induce vomiting. Call a physician or Poison Control Center.

INHALATION: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician or Poison Control Center if you feel unwell.

NOTES TO PHYSICIAN: Treat symptomatically. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action should be taken involving any personal risk or without suitable training.

EXTINGUISHING MEDIA: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

OTHER CONSIDERATIONS: In a fire or if heated, a pressure increase will occur and the container may burst.

EXPLOSION HAZARDS: None Expected.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: None Expected.

SENSITIVITY TO IMPACT: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products may include the following materials: carbon dioxide, carbon monoxide, metal oxide/oxides

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if not water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

GENERAL PROCEDURES: No action should be taken involving and personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. put on appropriate personal protective equipment.

RELEASE NOTES: Do not flush into surface water or sanitary sewer system.

SPECIAL PROTECTIVE EQUIPMENT: Avoid breathing vapors and provide adequate ventilation. As conditions warrant, wear a NIOSH approved self-contained breathing apparatus, or respirator, and appropriate personal protection (rubber boots, safety goggles, and heavy rubber gloves).

7. HANDLING AND STORAGE

HANDLING: Ensure adequate ventilation. Wear personal protective equipment as required based on a risk assessment. Do not

get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

STORAGE: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food or drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SPECIAL SENSITIVITY: Incompatible Products - Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
2- Butoxyethanol	TWA	50	240	20	97	NL	NL
	STEL					NL	NL

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: If splashes are likely to occur, wear: Tightly fitting safety goggles and face shield

SKIN: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

RESPIRATORY: If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Typical

ODOR THRESHOLD: No data available

APPEARANCE: Colored Liquid

pH: 13 to 14

FLASH POINT AND METHOD: > (200°F)

AUTOIGNITION TEMPERATURE: No data available

VAPOR PRESSURE: 20 mm/hg at (70°F)

VAPOR DENSITY: Heavier than Air

BOILING POINT: (212°F) to (431°F)

FREEZING POINT: No data available

MELTING POINT: No data available

POUR POINT: No data available

THERMAL DECOMPOSITION: No data available

SOLUBILITY IN WATER: Completely soluble

EVAPORATION RATE: No data available

DENSITY: No data available

SPECIFIC GRAVITY: 1.06 to 1.08

VISCOSITY: No data available

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions.

POLYMERIZATION: Hazardous polymerization does not occur.

CONDITIONS TO AVOID: None known based on information supplied.

POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of storage and use, hazardous reactions will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition can lead to release of irritating gases and vapors.

INCOMPATIBLE MATERIALS: Strong oxidizing agents. Strong bases.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Causes serious eye irritation.

SKIN EFFECTS: Causes severe skin burns.

SENSITIZATION: No data available

REPRODUCTIVE EFFECTS: No data available

TARGET ORGANS: No data available

MUTAGENICITY: No data available

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available

ECOTOXICOLOGICAL INFORMATION: No data available

AQUATIC TOXICITY (ACUTE): No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

EMPTY CONTAINER: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Liquid N.O.S.

TECHNICAL NAME: (Contains: Caustic Potash)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN1760

PACKING GROUP: III

LABEL: Corrosive

OTHER SHIPPING INFORMATION: All products offered for domestic ground transportation that meet the following Exceptions for Class 8 (corrosive materials) will be packaged and shipped as "Limited Qty".

(1) For corrosive materials in Packing Group II, inner packagings not over 1.0 L (0.3 gallon) net capacity each for liquids or not over 1.0 kg (2.2 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.

(2) For corrosive materials in Packing Group III, inner packagings not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs

or less.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: No data available

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: No

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Potassium Hydroxide	< 10	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2- Butoxyethanol	111-76-2
Potassium Hydroxide	1310-58-3

16. OTHER INFORMATION


PREPARED BY: KH Date Revised: 6/2/2015

REVISION SUMMARY: This SDS replaces the 6/2/2015 SDS. Revised: **Section 8:** ENGINEERING CONTROLS. **Section 9:** ODOR, (VOC). **Section 10:** POSSIBILITY OF HAZARDOUS REACTIONS. **Section 15:** ACUTE, CHRONIC, FIRE, PRESSURE GENERATING, REACTIVITY.

HMIS RATING

HEALTH	<input type="text" value=""/>	<input type="text" value="2"/>
FLAMMABILITY	<input type="text" value=""/>	<input type="text" value="0"/>
PHYSICAL HAZARD	<input type="text" value=""/>	<input type="text" value="1"/>
PERSONAL PROTECTION	<input type="text" value="B"/>	

NFPA CODES



MANUFACTURER DISCLAIMER: The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.