

ANCHOR

STEEL REINFORCED REPAIR PUTTY



DESCRIPTION

ANCHOR is a steel reinforced, epoxy repair compound that you mix in your hands. It is designed to seal, mend, bond, and repair almost anything. **ANCHOR** hardens in minutes and can be used on a wide variety of surfaces. After curing, it can be filed, drilled, tapped, sanded, or painted. This product can even be used for repairs under water!

BENEFITS - FEATURES

- * Fast-acting
- * Can be used on a wide variety of surfaces
- * Easy-to-use
- * Material is 100% solid & will not shrink

- * Bonds in minutes
- * Repairs almost anything
- * Mixes in hands
- * Hardens like steel

ADVANTAGES

- * Cures in 1 hour
- * Works even under water
- * Can be: Sanded, tapped, drilled, filed, or painted

WHERE TO USE

- * Sink Traps
- * Cracked Porcelain
- * Leaking Pipes
- * Radiators
- * Gutters
- * Oil & Water Tanks
- * Ceramic Tile
- * Valves & Fittings
- * Bathroom Fixtures
- * Wood or Metal Furniture

RECOMMENDED FOR

- * Ferrous Metals
- * Wood
- * Porcelain
- * Fiber Glass
- * Non-Ferrous Metals
- * Glass
- * Concrete
- * Most Plastics

DIRECTIONS

Simply tear off the desired amount. Knead **Anchor** to a uniform color and apply it at once to the desired surface. For a smooth finish, hand rub with tap water or use a damp cloth prior to hardening.

When cured, **Anchor** can be painted, ground, filed, sanded, drilled, or tapped.

Wash hands and tools after use.

SPECIFICATIONS

Appearance.....Black and grey putty
Odor.....Generated during kneading

Melting point.....N/A
Solubility in water.....Insoluble

Flash point.....285°F
Shelf life.....2 yrs. if kept sealed

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

