

BUG-MASTER

DEMISE FIRE ANT KILLER



DESCRIPTION

This powdered insecticide zaps the life out of fire ants and other insects by literally draining them of their moisture. Just sprinkle some powder on or around ant hills and other entrances, then as soon as they track through it, the active ingredient silicon dioxide immediately begins to suck valuable moisture from their bodies. Best of all, if the insects are able to crawl back into the nest, the powder continues to cling to their bodies and contaminates the rest of the colony.

BENEFITS - FEATURES

- * Contains pyrethrin for quick knockdown
- * Powder clings to the body hairs of insects and is carried back to the nesting area.

ADVANTAGES

- * Works up to 6 months after application
- * Packaged in an easy-to-use puffer bottle

WHERE TO USE

- * Garages
- * Floor drains
- * Locker rooms
- * Mop Closets
- * Livestock Areas
- * Machine rooms
- * Storage rooms
- * Boiler rooms

RECOMMENDED USE

- * Hospitals
- * Restaurants
- * Schools
- * Bakeries
- * Supermarkets
- * Hotels
- * Motels
- * Warehouses
- * Sewage Plants
- * Bottling plants
- * Apartments

DIRECTIONS

FIRE ANTS: Sprinkle 2 tablespoons over fire ant mounds less than one foot in diameter and 3 tablespoons over mounds greater than one foot in diameter. For best results, apply when ants are active and avoid treatments in heavy dew or before rainfall. Do not disturb ants while applying this product. Do not water after application. Depending on the size of the mound, it may take up to one week to kill the fire ants. Repeat application only if ants reappear. It should not be used as a barrier treatment or as a prophylactic measure. Treat new mounds as they appear.

Ants, Pharaoh ants, Carpenter ants: Treat doors, around window frames, ant trails and hills, cracks and crevices and other areas of entry. Repeat as necessary.

Dry wood termites: To protect against entrance, using an electric or hand operated rotary duster, distribute this product through an entry, crawl hole into attic and crawl space of building, at a rate of 12 ounces per 1000 square feet. All vents and blowers on the windward side should be closed. Contact all wood surfaces. In case of localized infestations, probe to locate galleries and drill holes to inject this product into the galleries. If a reasonable heavy

infestation is suspected, professional treatment should be employed. Repeat as necessary.

Bees, hornets, yellow jackets and wasps: It is generally advisable to treat nests in the evening when insects are less active and have returned to the nest. Using hand or power duster or other suitable means, with extension tubes, if necessary, thoroughly dust nest and entrance and surrounding areas where insects alight. Nests in wall voids can be located by placing your ear against the wall. To treat, drill a hole in the area. For best results check nests carefully one or two days after treatment to ensure complete kill. Then remove and destroy nest to prevent emergence of newly hatched insects. If removal is not feasible, retreat the nest, if necessary. Do not use this product to treat overhead nests. Repeat as necessary.

Cockroaches, : Water bugs, Palmetto Bugs, Crickets, Fire brat, Silverfish, Book lice, Scorpions, Spiders, Centipedes, Sow bugs, Pill bugs, Earwigs, Clover Mites Lice and Millipedes: Distribute this products at the rate of 1.5 ounces per 100 square feet of surface area. Apply a continuous visible film to hiding places such as cracks and crevices, behind and beneath sinks, stoves, refrigerators, around

garbage cans, cabinets, along baseboards, door sills, frames and floors, around drains, pipes, plumbing, behind bookcases, storage and other utility installation. For severe infestations apply behind cabinets and walls, in crawl spaces and attics at a rate of 12 ounces per 1000 square feet. Repeat as necessary.

SEWER TREATMENTS: Cockroach infestations in sanitary sewer may be treated with approximately 4.5 ounces of this product per manhole. When treating sewers, one manhole per 200 feet or line should be treated. Treatments are made by removing the manhole cover and replacing with a disc of plywood bored to receive the usual flexible hose from portable to truck mounted ventilating equipment. 4.5 ounces of this product is introduced into the ventilating air to be dispersed quickly and thoroughly through the system. Repeat as necessary.

Read entire label on product be use. Additional application instructions on product.

SPECIFICATIONS

AppearanceWhite powder
Fragrance.....Plant extract
Ready to use.....Yes
Flash Point>200 F

pH.....6.6 @ 20% solution
Residual Duration.....Kills up to 6 months
Application.....Use a bulbous,
mechanical or electric duster

Active ingredients:

Pyrethrins.....1.00%
Piperonyl Butoxide, technical*.....10.00%
Silicon Dioxide.....60.00%
INERT INGREDIENTS.....29.00%
TOTAL.....100.00%

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

