

GLIDE

THERMOPLASTIC SPRAY BUFF



DESCRIPTION

This combination of detergents, thermoplastics, and solvents is the answer for achieving terrific looking floors. Simply, spray this buffing compound on floors and polish with a spray buff pad to easily remove black heel marks, scuffs, scratches, and dullness. It leaves a "wet look" gloss, and its exclusive, self-emulsifying system will not allow any build-up on floors. Regular use of this spray buff compound will reduce stripping and rewaxing procedures by over 75%. This product stops powdering and leaves the floor finish very hard and durable; yet, it is very slip-resistant. In addition, it may be used over most floor finishes successfully.

BENEFITS - FEATURES

- * Effective repair
- * Easy-to-use
- * Versatile

ADVANTAGES

- * Works on all types of floor finishes
- * For use with conventional and high-speed equipment
- * Lightly mist ahead of floor machine path and buff to a high shine

WHERE TO USE

- * For All Floors
- * For All Finishes
- * Use With Any Speed Floor Machine

RECOMMENDED FOR

- * Schools
- * Institutions
- * Hospitals
- * Nursing Homes
- * Restaurants
- * Cafeterias
- * Shopping Malls
- * Show Rooms
- * Office Buildings
- * Government Buildings
- * Hotels
- * Motels
- * Churches
- * Airports
- * Athletic/Country Clubs
- * Public Buildings

DIRECTIONS

1. Remove gross soil and dust mop the floor.
2. Spray a light mist of product on the floor in front of the floor machine. DO NOT OVER WET.
3. Using a nylon or polyester spray buff pad, buff the floor where the fine mist of spray buff has been applied.
4. Flip or change pad as necessary.
5. After spray buffing the floor is completed, dust mop the floor if dust is still present.

PLEASE NOTE: In order for spray buff to work correctly, three or four base coats of floor finish must be applied before using spray buff in order to achieve maximum gloss and wear properties. Heavy traffic areas may require dust mopping, followed by damp mopping, followed by spray buffing. Use of this spray buff will eliminate powdering and will never yellow the floor.

Requires no authorization by USDA prior to its use in offices and other similar nonprocessing areas.

SPECIFICATIONS

| | | |
|--------------------------------|------------------------------------|-------------------------------------|
| Fragrance.....Clean bouquet | Density.....8.41 lbs./gal. | Freeze/thaw Stability..... |
| Color (liquid).....Milky green | Heel mark resistance.....Excellent | Keep from freezing |
| Color (dry).....Clear | Buffability.....Excellent | |
| Gloss.....Excellent | Flash point.....None | Slip resistance(James Machine)..... |
| pH.....8.7 | Shelf life.....2 yr. min. | .61-.65 |

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

