QUICK-SIL

CAULKING - SEALANT

DESCRIPTION

QUICK-SIL is a silicone caulk and sealant ideal for use whenever a strong permanently elastic weatherproof caulk, sealant or adhesive is needed. Designed to seal non-porous surfaces around ceramic tile, cultured marble, showers, tubs, sinks and plumbing fixtures. Ideal for caulking windows, doors, silts and ceiling cracks and crevices. Features excellent adhesion and high chemical resistance. Will not sag or shrink during severe temperature changes. Useful for sealing cracks in machinery, heating and ventilation duct work, plumbing fixtures, electrical connections and low pressure water and drain lines. Bonds, name-plates, machinery flanges, glass, signs, electrical insulation etc. Offers unmatched performance under the most severe conditions. Remains flexible and will not shrink, crack, crumble or dry out.

BENEFITS - FEATURES

* Easy to use
* Eliminates waste
* Economical
* Seals
* Caulks
* Flexible
* Weatherproof
* Waterproof
* Bonds

ADVANTAGES

* Pressurized dispenser enable easy application.
* Flexible from -85ºF to +500ºF

WHERE TO USE

* Windows
* Tile
* Wood
* Rubber
* Ceramics
* Bathtubs
* Doors
* Marble
* Porcelain
* Plastic
* Plumbing
* Sinks

RECOMMENDED FOR

* Schools
* Institutions
* Hospitals
* Nursing Homes
* Restaurants
* Cafeterias
* Shopping Malls
* Show Rooms
* Office Buildings
* Government Buildings
* Hotels
* Motels
* Churches
* Airports
* Factories
* Country Clubs

DIRECTIONS

Read Material Safety Data Sheet before using.

1. Surface must be clean, dry and free of oil, tar, dirt and dust for best adhesion.
2. Hold can at 45º angle and apply a continuous bead of 1/16" to 1/8" to the mating surface.
3. Starts to cure immediately, fully cures in 24 hours and matches optimum strength in 7 days.

Note: After each use, leave a small bead of material, which will form a sealing"plug" for reuse. To use, gently pull and begin to use material. If "plug" breaks, leaving the dispensing tip sealed.

Use a paper clip or other wire object to remove and loosen the remainder of cured material.

SPECIFICATIONS

Color.....White
Clear
Appearance.....Paste
Odor.....Acetic Acid Odor

Specific gravity.....(H2O=1)@77: 1.03
Solubility in Water.....None

Flammabilty.....1
Shelf Life.....2 years

Another Exclusive Product of

ULTRACHEM INC.

Kansas City - Phoenix 800-451-0726

PHOSPHATE FREE
MADE IN ACCORDANCE WITH AND ACCEPTED FOR USE IN MEETING
OSHA
OPERATING STANDARDS WHEN ALL LABEL DIRECTIONS AND CAUTIONS ARE FOLLOWED
TESTED
APPROVED
NON-POLLUTANT