

# Steel One

## Safety Data Sheet

### SECTION 1: Product and company identification

Product name : Steel One  
Use of the substance/mixture : Premoistened wipe  
Product code : 1549  
Company : Ultra Chem Inc.  
PO Box 3827  
Shawnee, KS 66203 – USA  
T (913) 492-2929  
Emergency number : Infotrac 800-535-5053

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Skin Sens. 1 H317  
Asp. Tox. 1 H304  
Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : May be fatal if swallowed and enters airways  
May cause an allergic skin reaction  
Precautionary statements (GHS-US) : Avoid breathing fume  
Contaminated work clothing must not be allowed out of the workplace  
Wear eye protection, protective gloves  
If swallowed: Immediately call a doctor, a POISON CENTER  
If on skin: Wash with plenty of water  
Do NOT induce vomiting  
If skin irritation or rash occurs: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
Store locked up  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable  
Full text of H-phrases: see section 16

#### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	30 - 60	Flam. Liq. 4, H227 Asp. Tox. 1, H304
white mineral oil (petroleum)	(CAS No) 8042-47-5	15 - 40	Asp. Tox. 1, H304
(+)-limonene	(CAS No) 5989-27-5	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

# Steel One

## Safety Data Sheet

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove the victim into fresh air.
First-aid measures after skin contact	: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth with water. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: None under normal use.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Carbon dioxide. Dry chemical powder.
Unsuitable extinguishing media	: Do not use extinguishing media containing water.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Reactivity	: Upon combustion: CO and CO <sub>2</sub> are formed.

#### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Isolate from fire, if possible, without unnecessary risk.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Gloves. Protective clothing.
Emergency procedures	: Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Contain released substance, pump into suitable containers.
Methods for cleaning up	: This material and its container must be disposed of in a safe way, and as per local legislation.

#### 6.4. Reference to other sections

No additional information available

# Steel One

## Safety Data Sheet

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product.
- Hygiene measures : Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Store in a well-ventilated place. Keep cool. Store locked up.
- Incompatible products : Oxidizing agent.
- Incompatible materials : Sources of ignition. Heat sources.
- Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.
- Storage area : Meet the legal requirements.
- Special rules on packaging : meet the legal requirements.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### white mineral oil (petroleum) (8042-47-5)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
-------	--------------------------------	---------------------

#### 8.2. Exposure controls

- Personal protective equipment : Safety glasses. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Premoistened wipe.
- Odor : Citrus scent
- Odor threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : 197 °F Closed cup - Tested using the liquid component of the towelette
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : No data available
- Relative vapor density at 20 °C : No data available
- Specific gravity / density : 0.81 g/ml - Tested using the liquid component of the towelette
- Solubility : Liquid component is not soluble in water.
- Log Pow : No data available
- Log Kow : No data available

# Steel One

## Safety Data Sheet

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt - Tested using the liquid component of the towelette
Viscosity, dynamic	: No data available
VOC content	: < 3 % - Tested using the liquid component of the towelette

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

No additional information available

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

No additional information available

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

##### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
--------------------	---

##### (+)-limonene (5989-27-5)

LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight

##### white mineral oil (petroleum) (8042-47-5)

LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

##### (+)-limonene (5989-27-5)

IARC group	3 - Not Classifiable
------------	----------------------

##### white mineral oil (petroleum) (8042-47-5)

IARC group	3 - Not Classifiable
------------	----------------------

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: None under normal use.

# Steel One

## Safety Data Sheet

Symptoms/injuries after skin contact	: May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### 12.1. Toxicity

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)
(+)-limonene (5989-27-5)	
LC50 fish 1	720 µg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	702 µg/l (96 h; Pimephales promelas)
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)
white mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
Threshold limit algae 1	>= 100 mg/l (72 h; Pseudokirchneriella subcapitata; Growth rate)

#### 12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
(+)-limonene (5989-27-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.
ThOD	3.29 g O <sub>2</sub> /g substance
white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.

#### 12.3. Bioaccumulative potential

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
(+)-limonene (5989-27-5)	
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
white mineral oil (petroleum) (8042-47-5)	
Bioaccumulative potential	No bioaccumulation data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods	: Do not flush wipes.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

#### Additional information

Other information : No supplementary information available.

# Steel One

## Safety Data Sheet

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*