

# ANCHOR

## STEEL REINFORCED REPAIR PUTTY



### DESCRIPTION

**ANCHOR** is a steel reinforced, epoxy repair compound that you mix in your hands. It is designed to seal, mend, bond, and repair almost anything. **ANCHOR** hardens in minutes and can be used on a wide variety of surfaces. After curing, it can be filed, drilled, tapped, sanded, or painted. This product can even be used for repairs under water!

### BENEFITS - FEATURES

- \* Fast-acting
- \* Can be used on a wide variety of surfaces
- \* Easy-to-use
- \* Material is 100% solid & will not shrink

- \* Bonds in minutes
- \* Repairs almost anything
- \* Mixes in hands
- \* Hardens like steel

### ADVANTAGES

- \* Cures in 1 hour
- \* Works even under water
- \* Can be: Sanded, tapped, drilled, filed, or painted

### WHERE TO USE

- \* Sink Traps
- \* Cracked Porcelain
- \* Leaking Pipes
- \* Radiators
- \* Gutters
- \* Oil & Water Tanks
- \* Ceramic Tile
- \* Valves & Fittings
- \* Bathroom Fixtures
- \* Wood or Metal Furniture

### RECOMMENDED FOR

- \* Ferrous Metals
- \* Wood
- \* Porcelain
- \* Fiber Glass
- \* Non-Ferrous Metals
- \* Glass
- \* Concrete
- \* Most Plastics

### DIRECTIONS

Simply tear off the desired amount. Knead **Anchor** to a uniform color and apply it at once to the desired surface. For a smooth finish, hand rub with tap water or use a damp cloth prior to hardening.

When cured, **Anchor** can be painted, ground, filed, sanded, drilled, or tapped.

Wash hands and tools after use.

### SPECIFICATIONS

Appearance.....Black and grey putty  
Odor.....Generated during kneading

Melting point.....N/A  
Solubility in water.....Insoluble

Flash point.....285°F  
Shelf life.....2 yrs. if kept sealed

Another Exclusive Product of

**ULTRA-CHEM INC.**

Kansas City - Phoenix 800-451-0726

