

# ARMOUR

METALLIC INTERLOCKED POLYMER FLOOR FINISH



## DESCRIPTION

This floor finish is for those who want the **highest gloss and wear** with the **least amount of labor**. This 25% solids, metal cross linked, polymer finish gives your floors a depth of gloss like you've never seen before. **One coat does the job of two coats** of an ordinary finish. This durable finish is **detergent-resistant and non scuffing** which makes it a real labor-saver. It is suitable for use on all floors and may be maintained by damp mopping. This product performs exceptionally well with either spray buffing or high speed buffing, and its **excellent leveling** makes it easy to apply.

## BENEFITS - FEATURES

- \* Durability
- \* Self-leveling
- \* Appearance
- \* Versatile

## ADVANTAGES

- \* Extended wear and superior protection
- \* High-gloss, black mark, and detergent resistant
- \* Easy application with little or no mop drag
- \* May be used with or without floor sealer

## WHERE TO USE

- \* Resilient Flooring
- \* Terrazzo

## RECOMMENDED FOR

- \* Schools
- \* Institutions
- \* Hospitals
- \* Nursing Homes
- \* Restaurants
- \* Cafeterias
- \* Shopping Malls
- \* Show Rooms
- \* Office Buildings
- \* Government Buildings
- \* Hotels
- \* Motels
- \* Churches
- \* Airports
- \* Athletic/Country Clubs
- \* Public Buildings

## DIRECTIONS

**Read the entire label before using this product.**

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

### RESTORATIVE MAINTENANCE:

Completely remove all old wax, finish and soil from floor surface. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly

before applying additional coats, usually 20-30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 4 coats of finish is recommended.

**Note:** This product is a self-sealing finish, however, if tile is old, worn or porous, initially applying 1 -2 coats of a sealer will enhance gloss and long term performance.

### ROUTINE MAINTENANCE:

Sweep large debris and dust mop. Damp mop or automatic scrub using a neutral cleaner. Buff or burnish the floor to

enhance gloss as needed. Use Ultra-Chem Inc. Glide spray buff to extend time between re-coating.

### INTERIM MAINTENANCE:

Sweep large debris and dust mop. Top scrub with a maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above.

**Note:** Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

## SPECIFICATIONS

Fragrance.....Mild  
 Gloss.....1 coat 80-85  
                   2 coats 97-98  
 pH.....8.7  
 Density.....8.4 lbs./gal.  
 Leveling.....Excellent

Recoat.....Very good  
 Heel mark resistance.....Very good  
 Shelf life.....2 yr. min.  
 Freeze/thaw stability.....3 cycles  
 Powdering resistance.....Excellent  
 Drying time.....20-30 min.

Coverage.....3,000-4,000 sq. ft./gal.  
 Slip resistance  
 (James machine).....0.61-0.65  
 Total solids.....29.6%  
 Nonvolatile solids.....25%

Another Exclusive Product of

**ULTRA-CHEM INC.**

Kansas City - Phoenix 800-451-0726

