EZ-E

EXTREME TEMPERATURE, ANTI SEIZE



DESCRIPTION

This product is an all-purpose, anti seize lubricant and sealant that is formulated to be used wherever metal contacts metal. Its unique formula will withstand temperatures from -20°F to 2,100°F. Furthermore, it provides long-term protection even when it is exposed to damp or salty conditions. It prevents galling, pitting, seizing, fretting, galvanic action, and thread distortion even under extreme pressure. Best of all, it will not separate, evaporate, harden, wash off, or fuse to metal. In addition, this product also acts as a sealant and reduces friction; therefore, it makes tighter, firmer joints that open easier and reduce torque requirements.

BENEFITS - FEATURES

- * Effective under extreme temperatures
- * Acts as sealant and reduces friction
- * Provides long-term protection

ADVANTAGES

- * Withstands temperatures from -20°F to 2,100°F
- * Provides tighter, firmer joints that open easier and reduce torque requirements
- * Prevents galling, pitting, seizing, fretting, galvanic action, and thread distortion

WHERE TO USE

- * Engines
- * Copper
- * Shafts
- * Steel
- * Rubber
- * Aluminum
- * Motors
- * Boilers
- * Cast Iron
- * Brass
- * Plastic
- * Compressors
- * Exhaust Systems * Threaded Tubing

- * Schools
- * Automotive Dealers
- * Hotels/Motels
- * Foundries
- * Airports
- * Farmers
- * Refrigeration Companies
- * Offices

RECOMMENDED FOR

- * Restaurants
- * Bowling Alleys
- * Hospitals
- * Nursing Homes
- * Laundromats
- * Snow Removal Equipment

DIRECTIONS

SHAKE CAN UNTIL AGITATOR **MOVES FREELY**

Be sure surface to be treated is free of dirt, dust, oil, and grease. Spray 8 to 10 inches from surface. Apply an even coating of EZ-E. After spraying, invert can and spray short blast to clear valve.

Authorized by the USDA for use in federally inspected meat and poultry plants.

SPECIFICATIONS

Fragrance.....Mild, sweetish odor Appearance......Grey, viscous liquid Spray pattern.....Pinpoint Shelf life.....1 year min.

Storage stability.....120°F max. Boiling point......102°F vigorous boiling Flash point.....None up to boiling % volatile......67

Specific gravity......1.394 Solubility in water.....Negligible Vapor pressure......45 Net weight......12 oz.

Another Exclusive Product of



