

GLEAM

METALLIC INTERLOCKED, POLYMER FLOOR FINISH



DESCRIPTION

This medium-solids, acrylic polymer, metal cross linked floor finish provides an extraordinary value. This time-proven favorite has **outstanding gloss**, provides **excellent wear**, and is **highly resistant to black heel marks**. It meets or exceeds ASTM Standards for **slip resistance**. In addition, it provides a **durable coating** that **responds well to varied maintenance program procedures**. It may be spray buffed with either low or high-speed equipment, or mopped-on restoration with high-speed burnishing can be used. Furthermore, this product is easily removed with either conventional or no-rinse strippers.

BENEFITS - FEATURES

- * Durability
- * Appearance
- * High-gloss
- * Self-leveling
- * Versatile
- * Excellent wear
- * Resists black marks

ADVANTAGES

- * Extended wear and superior protection
- * Never yellows
- * May be used with or without floor sealer
- * Use on all resilient flooring as well as terrazzo, sealed wood, and some hard tile surfaces

WHERE TO USE

- * Resilient Flooring
- * Terrazzo

RECOMMENDED FOR

- * Schools
- * Hospitals
- * Show Rooms
- * Restaurants
- * Shopping Malls
- * Office Buildings
- * Motels
- * Airports
- * Hotels
- * Nursing Homes
- * Institutions
- * Cafeterias
- * Public Buildings
- * Government Buildings
- * Churches
- * Athletic & Country Clubs

DIRECTIONS

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

RESTORATIVE MAINTENANCE:

Completely remove all old wax, finish and soil from floor surface. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly

before applying additional coats, usually 20-30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 4 coats of finish is recommended.

ROUTINE MAINTENANCE:

Sweep large debris and dust mop. Damp mop or automatic scrub using a neutral cleaner. Buff or burnish the floor to enhance gloss as needed. Use Ultra-Chem Inc. Glide spray buff to extend time between re-coating.

INTERIM MAINTENANCE:

Sweep large debris and dust mop. Top scrub with a maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above.

Note: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

SPECIFICATIONS

Fragrance.....Mild	Density.....8.4 lb./gal.	Freeze/thaw stability.....3 cycles
Gloss.....Excellent	Leveling.....Excellent	Drying time.....20-30 min.
pH.....8.7	Recoatibility.....Very good	Coverage.....3,000-4,000 sq. ft./gal.
Shelf life.....2 yrs. min.	Heel mark resistance.....Very good	Slip resistance (James machine).....(.61-.65)

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

