

LOCK IT

METAL INTERLOCKED, ACRYLIC POLYMER FLOOR SEALER



DESCRIPTION

Before applying your floor finish or wax, this acrylic sealer is one of the wisest investments you can make. It is **very hard, durable, & detergent-resistant**; therefore, making it really tough! It may be used on all types of resilient tile, concrete, wood, terrazzo, and marble. Best of all, this product will save you money because it **seals the pores in the floor**; therefore, **less finish and wax is used**. Furthermore, it continues to protect your floor even after all finish and wax has been worn away. Not only will it protect your floors for years, but its **high-gloss** will **never yellow or powder**. In addition, it is compatible with every water-based finish or wax.

BENEFITS - FEATURES

- * Durable
- * Easy to apply
- * Compatible
- * Versatile
- * High-gloss

ADVANTAGES

- * Acrylic polymer provides long-lasting protection
- * Won't yellow or powder
- * Compatible with all water-based finishes or waxes
- * Enhances the appearance of the finish

WHERE TO USE

- * Terrazzo
- * Concrete
- * Resilient Tile
- * Marble

RECOMMENDED FOR

- * Schools
- * Hospitals
- * Show Rooms
- * Restaurants
- * Shopping Malls
- * Office Buildings
- * Motels
- * Airports
- * Hotels
- * Nursing Homes
- * Institutions
- * Cafeterias
- * Public Buildings
- * Government Buildings
- * Churches
- * Athletic & Country Clubs

DIRECTIONS

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. This product is of specific benefit in preparing old, worn or porous tile floors for finishing.

RESTORATIVE MAINTENANCE:

Completely remove all old wax, finish and soil from floor surface. Floor surface

must be clean, dry and free of residue before sealer is applied. Rinse with clean water if necessary. Apply sealer in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20-30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 2

coats of sealer is recommended. This sealer can be used as a finish coat, however, for a better shine, increased protection and easier maintenance, we recommended the application of 2 - 4 coats of Ultra-Chem Inc. floor finish that best fits your maintenance program.

Note: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

SPECIFICATIONS

Fragrance.....Characteristic	Color (dried film).....Clear	Density (lbs./gal.).....8.4
Color.....Milky white	Leveling.....Excellent	Nonvolatile solids.....16%
pH.....8.7	Coverage.....2,000 sq. ft./gallon	Total actives.....18.9%
Shelf life.....2 yrs. min.	Flash point.....None	

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

