

PRO-LONG

NON-MELT RED GREASE



DESCRIPTION

This product is a tough, durable, red, non soap, bentone base, non-melt grease. It is specially formulated with **extreme pressure and anti-wear additives** to provide heavy-duty service. This grease not only lubricates better, but because of its **tenacious film strength**, it **lasts longer** and **requires less frequent lubrication and replacement**. It is manufactured from **carefully selected base stocks** to meet the most critical industrial and commercial requirements. Furthermore, this lubricant has **excellent adhesive and cohesive properties** that **provide protection from corrosive atmospheres** including strong acids, alkalis, water, dirt, salt sprays, and steam.

BENEFITS - FEATURES

- * Exceptional adhesive & cohesive anti wear
- * Reduces shock and noise
- * Resistant to water, salt spray, and steam
- * Protects equipment indoors or outdoors
- * Non-melt
- * Seals out dust, dirt, & contaminants
- * Prolongs life of metal parts
- * Temperatures up to +550°F
- * Excellent load carrying capacity

ADVANTAGES

- * Will not melt or run at high operating temperatures
- * High shock and impact resistance
- * No pound out or thin out
- * Pumps equally well in low or high temperatures
- * Superior water resistance

WHERE TO USE

- * Ball & Roller Bearings
- * Sleeve Bearing
- * Cranes
- * Oven Conveyors
- * Wheel Bearings
- * Water Pumps
- * King Pins
- * Drag lines
- * Slides
- * Open Winches
- * Pillow Blocks
- * Roof Fans & Blowers

RECOMMENDED FOR

- * Golf Courses
- * Steel Mills
- * Elevators
- * Construction Equipment
- * Sewage Plants
- * Oil Fields
- * Air Conditioning
- * Mining
- * Marine
- * Farm Equipment
- * Street Departments
- * Road Departments
- * Cement Plants
- * Hospitals
- * Food Plants
- * Bottling Plants
- * Dairies
- * Industrial & Commercial Operations

SPECIFICATIONS

Color.....Red	Dropping point (ASTM D-556).....+550°F (non-melt)	Water Resistance.....Excellent
Penetration (ASTM D-217).....250-270	Timken OK load	Rust Resistance.....Excellent
NLGI grade.....2 to 2.5	(ASTM D-2509).....65 LB.	Acid Resistance.....Excellent

Another Exclusive Product of

ULTRA-CHEM INC.

Kansas City - Phoenix 800-451-0726

