

SAFETY DATA SHEET

ZAP

SECTION I - IDENTIFICATION

PRODUCT NAME: ZAP
PRODUCT CODE: A10-14000
COMPANY NAME: ULTRA-CHEM, INC.
ADDRESS: 9870 BRITTON ST
LENEXA, KS 66219
EMERGENCY PHONE: 800-535-5053
COMPANY PHONE: 800-451-0726
PRODUCT USE: Acoustical Ceiling Tile Restorer

SECTION II - HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Liquefied Gas
Skin Irritant: Category 2
Eye Irritant: Category 2A
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 14%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	10-30
Ethyl Alcohol	64-17-5	5-10%
Heptane	142-82-5	10-30%
Petroleum Distillates, hydrotreated light	64742-47-8	3-7%
Propane/n-Butane	68476-86-8	15-40%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

SAFETY DATA SHEET

ZAP

CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical or suitable for surrounding materials.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Wipe up small spill with towel and allow area to dry. excess may be removed after drying with sandpaper or other scraping device. dispose of residue in accordance with federal, state and local guidelines.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

OTHER PRECAUTIONS: Keep out of the reach of children. Follow label directions exactly. Vapors may collect in low lying areas.

INCOMPATIBILITY: Some plastics and painted surfaces, pre-test before using.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Ethyl Alcohol	1000 ppm	1000 ppm
Heptane	400 ppm	400 ppm
Petroleum Distillates, hydrotreated light	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

ENGINEERING CONTROLS / VENTILATION: Ambient ventilation suitable, forced ventilation should not be required

RESPIRATORY PROTECTION: Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Wash hands and all equipment thoroughly after use.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White Spray

ODOR: Hydrocarbon odor

ODOR THRESHOLD: N/D

BOILING POINT: N/D

FREEZING POINT: N/D

FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: N/D

AUTOIGNITION TEMPERATURE: N/D

SAFETY DATA SHEET

ZAP

LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
VAPOR PRESSURE (mm Hg): N/A
VAPOR DENSITY (AIR=1): > 2
EVAPORATION RATE: > 1
SPECIFIC GRAVITY (H2O=1): 0.87
pH: N/A
SOLIDS (%): 26%
SOLUBILITY IN WATER: 0%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILITY INCLUDING WATER (%): 80.8%
VOLATILE ORGANIC COMPOUNDS (VOC): 51%
DIELECTRIC STRENGTH (Volts): N/A
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.
INCOMPATIBILITY: Some plastics and painted surfaces, pre-test before using.
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Acetone** (67-64-1) LD₅₀ (Oral, Rat) 5800 mg/kg; LD₅₀ (Oral, Mouse) 3000 mg/kg; LD₅₀ (Oral, Rabbit) 5340 mg/kg; LC₅₀ (Inhalation, Rat, 8hr) 50100 mg/m³; LC₅₀ (Inhalation, Mouse, 4hr) 44,000 mg/m³ **Ethyl Alcohol** (64-17-5) LC₅₀ (Inhalation, Mouse, 4hr) 39 gr/m³; LC₅₀ (Inhalation, Rat, 10hr) 20,000 ppm; LD₅₀ (Oral, Mouse) 3450 mg/kg; LD₅₀ (Oral, Rabbit) 6300 mg/kg; LD₅₀ (Oral, Rabbit) 7060 mg/kg **Heptane** (142-82-5) LD₅₀ (Oral, Rat) 15,000 mg/kg; LC₅₀ (Inhalation, Rat, 4hr) 103 g/m³; LD₅₀ (Dermal, Rabbit) 2,000 mg/kg **Petroleum Distillates, hydrotreated light** (64742-47-8) LD₅₀ (Oral, Rat) 5 g/kg; LD₅₀ (Dermal, Rabbit) 2 g/kg; LC₅₀ (Rat, 4hr) 5 mg/L

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Causes irritation, defatting.

INGESTION: Causes gastrointestinal irritation, nausea, diarrhea, absorption through gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness.

INHALATION: Dizziness, headache, nausea, depression of central nervous system, prolonged exposure may lead to unconsciousness

SKIN: Causes localized defatting, irritation, dermatitis.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

CHRONIC HEALTH HAZARDS: May be toxic to kidneys and liver.

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **Acetone** (67-64-1) LC₅₀ (Trout, 96hr) 5540 mg/L; LC₅₀ (Bluegill, 96hr) 8300 mg/L; LC₅₀ (Fathead Minnow, 96hr) 7500 mg/L **Petroleum Distillates, hydrotreated light** (64742-47-8) Not expected to be harmful or demonstrate chronic toxicity toward aquatic organisms. Expected to be readily biodegradable. Do not contaminate water when disposing of equipment washwaters.

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: Components in this mixture can bioaccumulate in aquatic organisms.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: This material is toxic to aquatic life.

SAFETY DATA SHEET
ZAP

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES: Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: Ethyl Alcohol (64-17-5) acute, chronic, flammable.

STATE REGULATIONS: Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, **RTK** - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

INTERNATIONAL REGULATIONS: Acetone (67-64-1) Australia, China, Europe (EINECS), Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

NFPA HEALTH: 2
NFPA FLAMMABILITY: 3
NFPA REACTIVITY: 0
NFPA OTHER: None

HMIS HEALTH: 2
HMIS FLAMMABILITY: 3
HMIS REACTIVITY: 0
HMIS PROTECTION: B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis

DATE PREPARED: 01/14/2014

REVISION DATE: 11/26/2014

N/A = Not Applicable; N/D = Not Determined

SAFETY DATA SHEET ZAP

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.