# SAFETY DATA SHEET

## **PROTECT**

#### **SECTION I - IDENTIFICATION**

**PRODUCT NAME: PROTECT PRODUCT CODE:** A40-13050

**COMPANY NAME:** ULTRA-CHEM. INC. EMERGENCY PHONE: 800-535-5053

ADDRESS: 9870 BRITTON ST. LENEXA, KS 66219

**COMPANY PHONE:** 800-451-0726

ORDERS@ULTRA-CHEMINC.COM **COMPANY EMAIL:** 

PRODUCT USE: Battery acid cleaner

#### SECTION II - HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 1

Liquefied Gas

Eve Irritant: Category 2b

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol Contains gas under pressure; May explode if heated. Causes

eve irritation.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SYMBOL:

**HAZARDS NOT OTHERWISE CLASSIFIED: N/A** 

## SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT **CAS NUMBER PERCENT** 2-Butoxyethanol 111-76-2 1-5% Propane/n-Butane 68476-86-8 5-10% Isopropyl Alcohol 67-63-0 1-5%

## **SECTION IV - FIRST AID MEASURES**

**EYES:** Remove contact lenses. Flush with water for at least 15 minutes. See a physician if irritation persists.

**INGESTION**: Do not induce vomiting unless directed by medical authority. Immediately rinse mouth with water. Seek immediate medical attention.

**INHALATION**: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

**SKIN:** Wash thoroughly with soap and water. Seek medical attention if irritation develops.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

CHRONIC HEALTH HAZARDS: None known

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## **SECTION V – FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Dry chemical, carbon dioxide, foam, water spray for cooling.

**UNSUITABLE EXTINGUISHING MEDIA: N/A** 

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Avoid breathing smoke, fumes, and decomposition products. Cool fire exposed containers with water fog to prevent bursting.

> PAGE 1 of 4 A40-13050

## SAFETY DATA SHEET PROTECT

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

**HAZARDOUS COMBUSTION PRODUCTS: N/A** 

#### **SECTION VI – ACCIDENTAL RELEASE MEASURES**

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Absorb spill with non-combustible material such as vermiculite, sand or earth. **WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. **RCRA STATUS:** Product should be fully characterized prior to disposal (40 CFR 261).

## **SECTION VII - HANDLING AND STORAGE**

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding

50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

**OTHER PRECAUTIONS:** Keep out of the reach of children.

**INCOMPATIBILITY:** Strong acids, strong alkalis, strong oxidizing agents.

#### SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
2-Butoxyethanol	50 ppm	20 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Isopropyl Alcohol	500 ppm	400 ppm

ENGINEERING CONTROLS / VENTILATION: General ventilation and local exhaust recommended.

**RESPIRATORY PROTECTION:** Not required under normal use. If exposure levels are exceeded then organic vapor cartridge

respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

## **SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Orange Foam **ODOR:** Slight Ammonia odor **ODOR THRESHOLD:** N/D

**BOILING POINT:**  $> 212^{\circ}\text{F} (100^{\circ}\text{C})$ **FREEZING POINT:**  $< 32^{\circ}\text{F} (0^{\circ}\text{C})$ 

FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: N/D

AUTOIGNITION TEMPERATURE: N/D LOWER FLAMMABILITY LIMIT: N/D UPPER FLAMMABILITY LIMIT: N/D

**VAPOR PRESSURE (mm Hg):** 17.5 @ 77°F (25°C)

**VAPOR DENSITY (AIR=1):** < 1 **EVAPORATION RATE:** < 1

**SPECIFIC GRAVITY (H2O=1):** 1.00 @ 77° F (25° C)

**pH:** 10.8

SOLIDS (%): N/D

**SOLUBILITY IN WATER: 100%** 

PARTITION COEFFICIENT: n-OCTANOL/WATER (Kow): N/D

VOLATILITY INCLUDING WATER (%): > 80% VOLATILE ORGANIC COMPOUNDS (VOC): 16%

**DIELECTRIC STRENGTH (Volts):** N/A **DECOMPOSITION TEMPERATURE:** N/D

VISCOSITY: N/D

PAGE 2 of 4 A40-13050

## SAFETY DATA SHEET PROTECT

#### **SECTION X – STABILITY AND REACTIVITY DATA**

**REACTIVITY:** Chemically active metals and acids

**CHEMICAL STABILITY:** Stable

**CONDITIONS TO AVOID:** Temperatures greater than 122°F and sources of ignition.

**INCOMPATIBILITY:** Strong acids, strong alkalis, strong oxidizing agents. **HAZARDOUS DECOMPOSITION OR BY-PRODUCT:** Oxides of carbon

POSSIBLE HAZARDOUS REACTIONS: None Known

## **SECTION XI – TOXICOLOGICAL INFORMATION**

**TOXICOLOGICAL INFORMATION: 2-Butoxyethanol** (111-76-2) LD<sub>50</sub> (Oral, Rat) 470 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 4hr) 450 ppm; LD<sub>50</sub> (Dermal, Rabbit) 220 mg/kg **Isopropyl Alcohol** (67-63-0) LD<sub>50</sub> (Oral, Rat) 5045 mg/kg; LD<sub>50</sub> (Oral, Rabbit) 5045 mg/kg;

LD<sub>50</sub> (Dermal, Rabbit) 12,800 mg/kg; LC<sub>50</sub> (Inhalation, Rat, 8hr) 16,000 ppm

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

**EYES:** Causes mild irritation.

**INGESTION:** May cause gastrointestinal irritation, abdominal cramps.

INHALATION: Irritant. Avoid breathing spray mist. May cause irritation to respiratory tract.

SKIN: May cause mild irritation, dryness with prolonged or repeated contact.

MEDICAL CONDITION AGGRAVATED: None known

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

**CHRONIC HEALTH HAZARDS:** None known

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: No

#### **SECTION XII - ECOLOGICAL INFORMATION**

ECOLOGICAL INFORMATION: Isopropyl Alcohol (67-63-0) LC<sub>50</sub> (Fathead Minnow, 96 hrs) 100,000 mg/L

**BIODEGRADABILITY:** This product is biodegradable.

**BIOACCUMULATION:** This product is not expected to bioaccumulate.

**SOIL MOBILITY:** This product is mobile in soil. **OTHER ECOLOGICAL HAZARDS:** None Known

## **SECTION XIII - DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. **RCRA STATUS:** Product should be fully characterized prior to disposal (40 CFR 261).

#### **SECTION XIV - TRANSPORTATION INFORMATION**

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950 PACKAGING GROUP: N/A

AIR SHIPMENT

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1 **UN/NA NUMBER:** UN 1950

SHIPPING BY WATER: VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: N/A

PAGE 3 of 4 A40-13050

## SAFETY DATA SHEET PROTECT

#### **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: None

SARA 313 REPORTABLE INGREDIENTS: 2-Butoxyethanol (111-76-2)

**CLEAN WATER ACT: None** 

STATE REGULATIONS: California Proposition 65: None

INTERNATIONAL REGULATIONS: 2-Butoxyethanol (111-76-2) Europe (EINECS), Japan (ENCS), Australia (AICS), WHMIS

(Canada), DSCL (EEC), NDSL, Korea (ECL), Philippines (PICCS), New Zealand (NZIOC), China (IECS).

NFPA HEALTH: 1
NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 1
NFPA OTHER: None
HMIS HEALTH: 1
HMIS FLAMMABILITY: 1
HMIS REACTIVITY: 1
HMIS PROTECTION: A

#### **SECTION XVI - ADDTIONAL INFORMATION**

PREPARATION BY: Jonathon Jarvis DATE PREPARED: 11/15/2013 REVISION DATE: 06/10/2015

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.

PAGE 4 of 4 A40-13050