

SAFETY DATA SHEET
ULTRA FRESH METERED - OCEAN BREEZE

SECTION I - IDENTIFICATION

PRODUCT NAME: ULTRA-FRESH METERED SPRAY - OCEAN BREEZE
PRODUCT CODE: A40-14100
PRODUCT USE: Air Freshener
COMPANY NAME: ULTRA-CHEM, INC.
ADDRESS: 9870 BRITTON ST, LENEXA, KS 66219
COMPANY PHONE: 800-451-0726
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Liquefied Gas
Eye Irritant: Category 2A
Skin Irritant: Category 2
Specific Target Organ Toxicity (Single Exposure): Category 3
Skin Sensitization: Category 1

HAZARD STATEMENT(S): DANGER: Extremely Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin and serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. May cause an allergic skin reaction.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If on skin, wash with plenty of water. If skin irritation occurs, get medical advice or attention. Take off contaminated clothing and wash it before reuse. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing fumes, mist, vapor and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Dispose of contents and container in accordance with local, state and federal regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	40-80%
Propane/n-Butane	68476-86-8	10-30%
Fragrance	Mixture	1-5%

SECTION IV - FIRST AID MEASURES

EYES: Immediately flush with water for 15 minutes while holding eyelids open. Seek immediate medical attention.

INGESTION: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek medical attention.

INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

SKIN: Immediately wash with soap and water for 15 minutes. Seek medical attention if irritation persists.

ACUTE HEALTH HAZARDS: Acute, Inhalation of vapors may be narcotic or anesthetic. Ingestion of liquid will cause gastrointestinal distress, irritation, and possibly nausea. Liquid or vapors may be irritating to skin and eyes.

CHRONIC HEALTH HAZARDS: May cause damage to the following organs: kidneys, liver, skin, CNS depression.

NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, and alcohol foam.

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers. Shut off all sources of ignition.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Absorb with non-combustible material like vermiculite, sand or earth and rinse with small amount of soapy water. Do not allow to drain into sewers or storm drains. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use.

OTHER PRECAUTIONS: Keep out of the reach of children. Follow label instructions exactly. Avoid breathing fumes/vapors.

INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Propane/n-Butane	1000 ppm	1000 ppm
Fragrance	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear colorless spray mist

ODOR: Fresh Scent

ODOR THRESHOLD: N/D

BOILING POINT: >130°F

FREEZING POINT: N/D

FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: < 100°F

AUTOIGNITION TEMPERATURE: N/D

LOWER FLAMMABILITY LIMIT: N/A

UPPER FLAMMABILITY LIMIT: N/A

VAPOR PRESSURE (mm Hg): < 180 @ 70°F (21°C)

VAPOR DENSITY (AIR=1): < 2 @ 70°F (21°C)

EVAPORATION RATE: > 3 (Fast)
SPECIFIC GRAVITY (H₂O=1): 0.77 - 0.83 @ 77°F (25°C)
pH: N/A
SOLUBILITY IN WATER: Miscible
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILE ORGANIC COMPOUNDS (VOC): 25%
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: None Known
CHEMICAL STABILITY: Stable
CONDITIONS TO AVOID: Excess heat, open flame, sparks, electric equipment, ignition sources, and incompatible materials.
INCOMPATIBILITY: Strong oxidizing agents, strong reducing agents, some plastics.
HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon
POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Acetone (67-64-1) LD₅₀ (Oral, Rabbit) 5340 mg/kg; LD₅₀ (Dermal, Rabbit) 20000 mg/kg
ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin
EYES: Causes irritation, may cause conjunctivitis with possible corneal injury.
INGESTION: May cause gastrointestinal irritation, nausea, diarrhea, vomiting, aspiration hazard.
INHALATION: May cause irritation to the respiratory tract, dizziness, headaches, nausea, unconsciousness, central nervous system depression.
SKIN: May cause mild irritation, localized defatting, repeated prolonged contact may cause allergic reaction in some individuals.
MEDICAL CONDITION AGGRAVATED: Pre-existing conditions of the skin, liver, CNS, and kidneys
ACUTE HEALTH HAZARDS: Acute, Inhalation of vapors may be narcotic or anesthetic. Ingestion of liquid will cause gastrointestinal distress, irritation, and possibly nausea. Liquid or vapors may be irritating to skin and eyes.
CHRONIC HEALTH HAZARDS: May cause damage to the following organs: kidneys, liver, skin, CNS depression.
CARCINOGENICITY: OSHA: Not Classified ACGIH: A5 - Not suspected NTP: N/A IARC: N/A OTHER: N/A

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not Established
BIODEGRADABILITY: Component or components of this product are not biodegradable.
BIOACCUMULATION: Components in this mixture can bioaccumulate in aquatic organisms.
SOIL MOBILITY: This product is mobile in soil.
OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.
RCRA STATUS: Waste likely considered D001, under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.
HAZARD CLASS/DIVISION: 2.1
UN/NA NUMBER: UN 1950
PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Aerosols, Ltd.
Qty. **HAZARD CLASS/DIVISION:** 2.1

UN/NA NUMBER: UN 1950
PACKAGING GROUP: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Acetone (67-64-1) Reportable Quantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES: Fire Hazard

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, **RTK** - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH: 1

HMIS HEALTH: 1

NFPA FLAMMABILITY: 3

HMIS FLAMMABILITY: 3

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Chioma Agbai

DATE PREPARED: 10/14/2013

REVISION DATE: 04/27/2017

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliant.