SAFETY DATA SHEET LIFT-OFF

Date Prepared: 5/18/2015 SDS No: C10-21030-SDS Date Revised: 7/14/2023

Revision No: 2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: LIFT-OFF
PRODUCT CODE: C10-21030

DISTRIBUTED BY: ULTRA-CHEM, INC. 9870 BRITTON ST. LENEXA, KS 66219

Infotrac 800-535-5053

24 HR. EMERGENCY TELEPHONE NUMBERS

COMPANY PHONE: 800-451-0726

COMPANY EMAIL: ORDERS@ULTRA-CHEMINC.COM

GENERAL USE: Traffic Lane Cleaner

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion / Irritation, Category 1 Serious Eye Damage / Eye Irritation, Category 1

CHS I AREI

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)



Corrosion

SIGNAL WORD: DANGER HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENTS

Prevention:

P264: Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P314: Get medical advice/attention if you feel unwell.

Storage:

P404: Store in a closed container.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
2- Butoxyethanol	< 5	111-76-2
Sodium Polysilicate	< 5	1344-09-8
Sodium Hydroxide	< 5	1310-73-2
Fatty acids, tall-oil, sodium salts	< 5	61790-45-2

4. FIRST AID MEASURES

EYES: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. in case of contact with eyes, rinse immediately with plenty of water.

SKIN: Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower. Call a POISON CENTER or doctor / physician. Remove and wash contaminated clothing before re-use.

INGESTION: Rinse mouth. Do NOT induce vomiting. Call a physician or Poison Control Center.

INHALATION: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician or Poison Control Center if you feel unwell.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Product does not burn

GENERAL HAZARD: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action should be taken involving any personal risk or without suitable training.

EXTINGUISHING MEDIA: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

OTHER CONSIDERATIONS: In a fire or if heated, a pressure increase will occur and the container may burst.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products may include the following materials: carbon dioxide, carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if not water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

LARGE SPILL: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

7. HANDLING AND STORAGE

HANDLING: Ensure adequate ventilation. Wear personal protective equipment as required based on a risk assessment. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before reuse. Wash thoroughly after handling.

STORAGE: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food or drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)									
		EXPOSURE LIMITS							
		OSHA PEL		ACGIH TLV		Supplier OEL			
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³		
2- Butoxyethanol	TWA	50	240	20	97	NL	NL		
	STEL					NL	NL		
Sodium Hydroxide	TWA		2			NL	NL		
	STEL					NL	NL		

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: If splashes are likely to occur, wear: Tightly fitting safety goggles and face shield

SKIN: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

RESPIRATORY: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

PROTECTIVE CLOTHING: Wear chemical protective clothing e.g. gloves, aprons, boots. As conditions required.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Fragranced

ODOR THRESHOLD: No data available

APPEARANCE: Colored Liquid

pH: 11 to 13

FLASH POINT AND METHOD: > (200°F)

FLAMMABLE LIMITS: 0 to 0
Notes: NA = Not Applicable

AUTOIGNITION TEMPERATURE: NA = Not Applicable

VAPOR PRESSURE: 1 VAPOR DENSITY: 1 BOILING POINT: (212°F) FREEZING POINT: (32°F)

SOLUBILITY IN WATER: Completely soluble **EVAPORATION RATE:** Similar to water

SPECIFIC GRAVITY: 1
VISCOSITY: Water thin

(VOC): 5.000

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions.

POLYMERIZATION: Hazardous polymerization does not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxodies

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS: Eye Damage/Irritation **SKIN EFFECTS:** Causes skin irritation.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This material has not been tested for acute environmental effects. **BIOACCUMULATION/ACCUMULATION:** No evidence to suggest bio-accumulation will occur.

DISTRIBUTION: No data available

CHEMICAL FATE INFORMATION: No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: This material, as supplied, is not a hazardous waste according to federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixing with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Corrosive Liquid N.O.S.

TECHNICAL NAME: (Contains: Caustic Soda)

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: UN1760
PACKING GROUP: III

NAERG: 154

LABEL: Corrosive

OTHER SHIPPING INFORMATION: All products offered for domestic ground transportation that meet the following Exceptions for Class 8 (corrosive materials) will be packaged and shipped as "Limited Qty".

- (1) For corrosive materials in Packing Group II, inner packagings not over 1.0 L (0.3 gallon) net capacity each for liquids or not over 1.0 kg (2.2 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.
- (2) For corrosive materials in Packing Group III, inner packagings not over 5.0 L (1.3 gallon) net capacity each for liquids or not over 5.0 kg (11 lbs) net capacity each for solids, packed in a strong outer packaging with a gross package weight of 66 lbs or less.

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: Yes CHRONIC: No

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Sodium Hydroxide	< 5	1,000

TSCA (TOXIC SUBSTANCE CONTROL ACT)


Chemical Name	CAS
2- Butoxyethanol	111-76-2
Sodium Polysilicate	1344-09-8
Sodium Hydroxide	1310-73-2
Fatty acids, tall-oil, sodium salts	61790-45-2

CALIFORNIA PROPOSITION 65: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

PREPARED BY: KH Date Prepared: 5/18/2015





MANUFACTURER DISCLAIMER: The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. the information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.